



Material Safety Data Sheet

This MSDS is prepared in accordance with OSHA 29 CFR 1910.1200



WHMIS Class E: Corrosive liquid. WHMIS CLASS D-2: Material causing other toxic effects. WHMIS Class B-3: Combustible liquid with a flash point between 37.8°C (100°F) and 93.3°C (200°F).

Class: Irritating substance.
Class: Corrosive material
Class: Combustible liquid II having a flash point between 37.8°C (100°F) and 60.0°C (140°F).

WHMIS (Pictograms)

WHMIS (Classification)

HCS

Section 1. Chemical Product and Company Identification

Product Name/ Trade name **Quat Stat SC**

Code **340**

Synonym Disinfectant/ Deodorant/ Virucide

CAS # Mixture.

Chemical Family Not available.

Validation Date **3/26/2004**

Chemical Formula Not applicable.

Print Date **3/27/2004**

Manufacturer/ Supplier Betco Corporation
1001 Brown Avenue
Toledo, Oh 43607
(419) 241-2156

In Case of Emergency Chemtrec (800) 424-9300

TSCA TSCA Inventory: All components listed or are exempt from listing.

DSL/ NDSL All components listed unless noted elsewhere on this MSDS

Protective Clothing



Section 2. Composition and Information on Ingredients

Name	CAS #	% by Weight	Exposure Limits	LC ₅₀ /LD ₅₀
1) Quaternary Ammonium Chloride	68424-95-3	10-15	Not available.	Not available.
2) Quaternary Ammonium Chloride	68424-85-1	5-10	Not available.	Not available.
3) Nonionic Surfactant	9016-45-9	5-10	Not available.	Not available.
4) Ethyl Alcohol	64-17-5	0-5	TWA: 1000 (ppm) TWA: 1000 (ppm) from OSHA (PEL) [United States]	ORAL (LD50): Acute: 7060 mg/kg [Rat].

Section 3. Hazards Identification

Potential Acute Health Effects Very hazardous in case of skin contact (corrosive, irritant), of eye contact (irritant, corrosive). Hazardous in case of ingestion, of inhalation. Liquid or spray mist may produce tissue damage particularly on mucous membranes of eyes, mouth and respiratory tract. Skin contact may produce burns. Inhalation of the spray mist may produce severe irritation of respiratory tract, characterized by coughing, choking, or shortness of breath. Inflammation of the eye is characterized by redness, watering, and itching. Skin inflammation is characterized by itching, scaling, reddening, or, occasionally, blistering.

Potential Chronic Health Effects Repeated or prolonged contact with spray mist may produce chronic eye irritation and severe skin irritation. Over-exposure by inhalation may cause respiratory irritation.

Carcinogenic Effects Not classified or listed by IARC, NTP, OSHA, EU and ACGIH.

Section 4. First Aid Measures

Eye Contact	Hold eye open and rinse slowly and thoroughly with water for 15 to 20 minutes. Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eye. Call a poison control center or doctor immediately for treatment advice.
Skin Contact	Rinse skin with plenty of water for 15 to 20 minutes. Call a poison control center or doctor for further treatment advice.
Inhalation	Move person to fresh air. If person is not breathing, call 911 or an ambulance, then give artificial respiration., preferably mouth to mouth if possible. Call a poison control center or doctor for further treatment advice.
Ingestion	Call a poison control center immediately for treatment advice. Have person sip a glass of water if able to swallow. Do NOT induce vomiting unless instructed to do so by a poison control center or doctor. Do not give anything by mouth to an unconscious person

Section 5. Fire Fighting Measures

Products of Combustion	These products are carbon oxides (CO, CO2).
Fire Fighting Media and Instructions	Use DRY chemicals, CO2, alcohol foam or water spray.
Special Remarks on Fire Hazards	Not available.
Special Remarks on Explosion Hazards	Not available.

Section 6. Accidental Release Measures

Small Spill and Leak	Dilute with water and mop up, or absorb with an inert dry material and place in an appropriate waste disposal container.
Large Spill and Leak	Combustible liquid. Corrosive liquid. Keep away from heat. Keep away from sources of ignition. Stop leak if without risk. Absorb with DRY earth, sand or other non-combustible material. Do not touch spilled material. Use water spray curtain to divert vapor drift. Prevent entry into sewers, basements or confined areas; dike if needed.
Personal Protection in Case of a Large Spill	Splash goggles. Full suit. Boots. Gloves. Suggested protective clothing might not be sufficient; consult a specialist BEFORE handling this product.

Section 7. Handling and Storage

Precautions	Keep container dry. Keep away from heat. Keep away from sources of ignition. Ground all equipment containing material. Do not ingest. Do not breathe gas/fumes/ vapor/spray. In case of insufficient ventilation, wear suitable respiratory equipment. If ingested, seek medical advice immediately and show the container or the label. Avoid contact with skin and eyes. Keep away from incompatibles such as oxidizing agents.
Incompatibility	Reactive with oxidizing agents.
Storage	Corrosive materials should be stored in a separate safety storage cabinet or room. Keep out of the reach of children. Not for use or storage in or around the home.

Section 8. Exposure Controls/Personal Protection

Engineering Controls	Good general ventilation should be sufficient to control airborne levels.
Personal Protection	
<i>Eyes</i>	Splash goggles.
<i>Body</i>	Lab coat.
<i>Respiratory</i>	Wear appropriate respirator when ventilation is inadequate.
<i>Hands</i>	Gloves (impervious).

**Protective Clothing
(Pictograms)**



Exposure Limits

Ethyl Alcohol

TWA: 1000 (ppm)

TWA: 1000 (ppm) from OSHA (PEL) [United States]

Consult local authorities for acceptable exposure limits.

Section 9. Physical and Chemical Properties

Physical State and Appearance	Liquid.	Odor	Pleasant.
Molecular Weight	Not applicable.	Taste	
pH	13 [Basic.]	Color	Violet.
Boiling/Condensation Point	Not available.		
Melting/Freezing Point	Not available.		
Critical Temperature	Not available.		
Instability Temperature	Not available.		
Specific Gravity	1.01 (Water = 1)		
Vapor Pressure	Not Determined		
Vapor Density	Not Determined		
Volatility	Not available.		
VOC	Not available.		
Evaporation Rate	Not available.		
Dispersion Properties	See solubility in water.		
Solubility	Soluble in cold water, hot water.		
The Product is:	COMBUSTIBLE.		
Auto-ignition Temperature	Not available.		
Flash Points	CLOSED CUP: 51.667°C (125°F). (Tagliabue.)		
Flammable Limits	Not available.		
Fire Hazards in Presence of Various Substances	Not available.		
Explosion Hazards in Presence of Various Substances	Explosive in presence of open flames and sparks, of heat.		

Section 10. Stability and Reactivity Data

Stability	The product is stable.
Incompatibility with Various Substances	Reactive with oxidizing agents.
Hazardous Decomposition Products	Not available.

Section 11. Toxicological Information

Routes of Entry	Absorbed through skin. Eye contact. Inhalation. Ingestion.
Toxicity to Animals	Acute oral toxicity (LD50): 3030 mg/kg [Rat]. (Tetrasodium salt of ethylenediaminetetraacetic acid).
Acute Effects on Humans	<p>Eyes Very hazardous in case of eye contact (irritant, corrosive). Inflammation of the eye is characterized by redness, watering, and itching. May cause corneal opacity.</p> <p>Skin Sensitization of the product: Not available. Very hazardous in case of skin contact (corrosive, irritant). Skin contact may produce burns. Skin inflammation is characterized by itching, scaling, reddening, or, occasionally, blistering.</p> <p>Inhalation Hazardous in case of inhalation. Inhalation of the spray mist may produce severe irritation of respiratory tract, characterized by coughing, choking, or shortness of breath. Over-exposure by inhalation may cause respiratory irritation.</p> <p>Ingestion May be fatal if swallowed. May cause burns to mouth, throat, and stomach. May cause headache, dizziness, nausea, and loss of concentration.</p>
Chronic Effects on Humans	Repeated or prolonged contact with spray mist may produce chronic eye irritation and severe skin irritation. Over-exposure by inhalation may cause respiratory irritation.
Special Remarks on Toxicity to Animals	Not available.
Special Remarks on Chronic Effects on Humans	Not available.

Section 12. Ecological Information

Ecotoxicity	Not available.
BOD5 and COD	Not available.
Products of Biodegradation	These products are carbon oxides (CO, CO2) and water.
Toxicity of the Products of Biodegradation	The products of degradation are less toxic than the product itself.
Special Remarks on the Products of Biodegradation	Not available.

Section 13. Disposal Considerations

Waste Information	Dispose of in accordance with all applicable local, state and Federal regulations
Waste Stream	Not available.

Section 14. Transport Information

DOT (U.S.A) (Pictograms)



TDG Classification

Class 8: Corrosive material



PIN UN, Proper Shipping Name, PG

Shipping name: CORROSIVE LIQUIDS, N.O.S. UNNA: 1760 PG: III

Maritime Transportation

Not available.

Special Provisions for Transport

Not available.

Section 15. Other Regulatory Information and Pictograms

WHMIS (Classification)

WHMIS Class E: Corrosive liquid. WHMIS CLASS D-2: Material causing other toxic effects. WHMIS Class B-3: Combustible liquid with a flash point between 37.8°C (100°F) and 93.3°C (200°F).



Regulatory Lists

CEPA DSL: No products were found.

Other Regulations

OSHA: Hazardous by definition of Hazard Communication Standard (29 CFR 1910.1200).

Other Classifications

HCS (U.S.A.)

Class: Irritating substance.
Class: Corrosive material
Class: Combustible liquid II having a flash point between 37.8°C (100°F) and 60.0°C (140°F).

USA Regulatory Lists

California prop. 65: This product contains the following ingredients for which the State of California has found to cause reproductive harm (female) which would require a warning under the statute: Ethylene Oxide < 1 ppm
California prop. 65: This product contains the following ingredients for which the State of California has found to cause cancer which would require a warning under the statute: Ethylene Oxide < 1 ppm
Massachusetts RTK: Ethylene Oxide

DSD (EEC)

R10- Flammable.


International Regulations Lists

No products were found.

Hazardous Material Information System (U.S.A.)

Health	3
Flammability	2
Physical Hazard	0

National Fire Protection Association (U.S.A.)



The Hazard Ranking systems presented on this MSDS provide only a quick reference for hazard information. The ENTIRE MSDS must be consulted to determine any specific hazards, First Aid measures, and PPE associated with this product.

Section 16. Other Information

Validated by CRushton on 3/26/2004.

Verified by CRushton.

Printed 3/27/2004.

Information Contact **Betco Corporation**
1001 Brown Avenue
Toledo, Ohio 43607

Notice to Reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

Validated on 3/26/2004.

Quat Stat SC**Page: 6/6****Continued on Next Page**