

Material Safety Data Sheet

This MSDS is prepared in accordance with OSHA 29 CFR 1910.1200

(1)

Not controlled under WHMIS (Canada).

HCS Class: Irritating substance.

WHMIS (Pictograms)

WHMIS (Classification)

HCS

Section 1. Chemical Product and Company Identification			
Product Name/ Trade name	Clear Image	Code	092
Synonym	Non-Ammoniated Glass/Plexiglass® Cleaner	CAS#	Mixture.
Chemical Family	Not available.	Validation Date	3/20/2004
Chemical Formula	Not applicable.	Print Date	3/27/2004
Manufacturer/ Supplier	Betco Corporation 1001 Brown Avenue Toledo, Oh 43607 (419) 241-2156	In Case of Cho Emergency	emtrec (800) 424-9300
TSCA	TSCA Inventory: All components listed or are exempt from listing.		
DSL/ NDSL	All components listed unless noted elsewhere on this MSDS	Pr	rotective Clothing



Section 2. Composition and Information on Ingredients				
Name	CAS#	% by Weight	Exposure Limits	LC_{50}/LD_{50}
1) Ethyl Alcohol	64-17-5	15-20	TWA: 1000 (ppm) TWA: 1000 (ppm) from OSHA (PEL) [United States]	ORAL (LD50): Acute: 7060 mg/kg [Rat].
2) 2-Butoxyethanol	111-76-2	0-5	TWA: 20 (ppm) from ACGIH (TLV) [United States] TWA: 50 (ppm) from OSHA (PEL) [United States]	ORAL (LD50): Acute: 1746 mg/kg [Rat].
3) Sodium Lauryl Sulfate	151-21-3	0-5	Not available.	Not available.
4) Monoethanolamine	141-43-5	0-5	TWA: 3 (ppm) TWA: 6 (ppm) from OSHA (PEL) [United States] STEL: 6 (ppm)	Not available.
5) Liquified Petroleum Gas	68476-85-7	0-5	TWA: 1000 (ppm) TWA: 1000 (ppm) from OSHA (PEL) [United States]	Not available.
6) Nonionic Surfactant	127087-87-0	0-5	Not available.	Not available.
7) Perfume Oil	N/A	0-5	Not available.	Not available.

Potential Acute Health Effects No specific information is available in our database regarding the acute toxic effects of this material for

humans.

Potential Chronic Health

Effects

Over-exposure by inhalation may cause respiratory irritation. Severe over-exposure can produce lung

damage, choking, unconsciousness or death.

Carcinogenic Effects Not classified or listed by IARC, NTP, OSHA, EU and ACGIH.

Section 4. First Aid Measures		
Eye Contact	Flush eyes with large quantities of water. Seek medical attention if irritation persists.	
Skin Contact	Flush with large quantities of water. Seek medical attention if irritation persists.	
Inhalation	Get to fresh air. Seek medical attention if irritation persists.	
Ingestion	Drink two glasses of water. Do not induce vomiting. Seek medical attention immediately.	

Section 5. Fire Fighting Measures		
Products of Combustion	Not available.	
Fire Fighting Media and Instructions	CO2, dry chemical, foam.	
Special Remarks on Fire Hazards	N/A	
Special Remarks on Explosion Hazards	Heated cans may burst.	

Section 6. Accidental Release Measures		
Small Spill and Leak	N/A	
Large Spill and Leak	Absorb with an inert material and put the spilled material in an appropriate waste disposal. Call for assistance on disposal.	
Personal Protection in Case of a Large Spill	Splash goggles. Full suit. Boots. Gloves. Suggested protective clothing might not be sufficient; consult a specialist BEFORE handling this product.	

Section 7. Handling and Storage		
Precautions	Keep away from heat. Keep away from sources of ignition. Empty containers pose a fire risk, evaporate the residue under a fume hood. Ground all equipment containing material. Do not ingest. Do not breathe gas/fumes/ vapor/spray. Wear suitable protective clothing. If ingested, seek medical advice immediately and show the container or the label.	
Incompatibility	None known.	
Storage	Keep out of the reach of children. Not for use or storage in or around the home.	

Section 8. Exposure Controls/Personal Protection		
Engineering Controls	Good general ventilation should be sufficient to control airborne levels.	
Personal Protection		
Eyes	Safety glasses.	
Body	Lab coat.	
Respiratory	Not applicable.	
Hands	Gloves.	
Protective Clothing (Pictograms)		

Exposure Limits

Ethyl Alcohol

TWA: 1000 (ppm)

TWA: 1000 (ppm) from OSHA (PEL) [United States]

2-Butoxyethanol

TWA: 25 (ppm)

TWA: 50 (ppm) from OSHA (PEL) [United States]

Monoethanolamine

TWA: 3 (ppm)

TWA: 6 (ppm) from OSHA (PEL) [United States]

STEL: 6 (ppm)

Liquified Petroleum Gas

TWA: 1000 (ppm)

TWA: 1000 (ppm) from OSHA (PEL) [United States]

Consult local authorities for acceptable exposure limits.

Section 9. Physical and Chemical Properties			
Physical State and Appearance	Liquid.	Odor	Characteristic.
Molecular Weight	Not applicable.	Taste	
pН	10.5 to 11.5 [Basic.]	Color	White.
Boiling/Condensation Point	N/A		
Melting/Freezing Point	Not available.		
Critical Temperature	Not available.		
Instability Temperature	Not available.		
Specific Gravity	Not available.		
Vapor Pressure	50 psig @ 68°F		
Vapor Density	>1 (Air = 1)		
Volatility	99		
voc	Not available.		
Evaporation Rate	<1		
Dispersion Properties	See solubility in water.		
Solubility	Easily soluble in cold water.		
The Product is:	May be combustible at high temperature.		
Auto-ignition Temperature	Not available.		
Flash Points	Not available.		
Flammable Limits	LOWER: 1.1% UPPER: 19%		
Fire Hazards in Presence of Various Substances	Not available.		
Explosion Hazards in Presence of Various Substances	Containers may explode when heated.		

Section 10. Stability and Reactivity Data	
Stability	The product is stable.
Incompatibility with Various Substances	None known.
Hazardous Decomposition Products	Will not occur.

Section 11. Toxicolog	ical Information
Routes of Entry	Not available.
Toxicity to Animals	Acute oral toxicity (LD50): 1746 mg/kg [Rat]. (2-Butoxyethanol).
Acute Effects on Humans	
Eyes	Eye irritant. Liquid and mist may damage the eyes causing corneal injury.
Skin	Skin irritant. May cause moderate redness and swelling.
Inhalation	May be irritating to mucous membranes of the nose, throat, and lungs.
Ingestion	May cause dizziness, headache, nausea, vomiting, and diarrhea.
Chronic Effects on Humans	Over-exposure by inhalation may cause respiratory irritation. Severe over-exposure can produce lung damage, choking, unconsciousness or death.
Special Remarks on Toxicity to Animals	Not available.
Special Remarks on Chronic Effects on Humans	Not available.

Section 12. Ecological Information		
Ecotoxicity	Not available.	
BOD5 and COD	Not available.	
Products of Biodegradation	Possibly hazardous short term degradation products are not likely. However, long term degradation products may arise.	
Toxicity of the Products of Biodegradation	Not available.	
Special Remarks on the Products of Biodegradation	Not available.	

Section 13. Disposal Considerations			
Waste Information	Waste must be disposed of in accordance with federal, state and local environmental control regulations.		
Waste Stream	Not available.		

Section 14. Transport Information

DOT (U.S.A) (Pictograms)



PIN UN, Proper Shipping Not applicable.
Not available.

Special Provisions for Transport

Not applicable.

Not applicable.

Not applicable.

WHMIS (Classification)	Not controlled under Wi	HMIS (Canada).	Ţ	
Regulatory Lists				
Other Regulations	Not available. or of its ingredients			
Other Classifications	HCS (U.S.A.)	HCS Class: Irritating substance.		
	USA Regulatory Lists			
		SARA 311/312 MSDS distribution - chemical inventory - hazard identification 2-Butoxyethanol: immediate health hazard, delayed health hazard SARA 313 toxic chemical notification and release reporting: 2-Butoxyethan		
	DSD (EEC)	This product is not classified according to the EU regulations.		
	International Regulations Lists	No products were found.		
Hazardous Material Information System (U.S.A.)	Health Flammability Physical Hazard	* 2 National Fire Protection Association (U.S.A.)	Flammability Health 2 1 Instability	

Section 16. Other Information Validated by CRushton on 3/20/2004. Verified by CRushton. Printed 3/27/2004. Information Contact Betco Corporation 1001 Brown Avenue Toledo, Ohio 43607 Notice to Reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

Validated on 3/20/2004.	Clear Image	Page: 6/6
	orom mage	

Continued on Next Page