

SECTION I: PRODUCT INFORMATION

Product Name or Number (as it appears on label): AQUASPORT WOOD FLOOR CLEANER Product Number: 5837			Product Divisio Janitorial	n:	
Spartan Chemical Company, Inc. Product/Technical Info			ormation:1-(800)-537-899	00	
1110 Spartan Drive		Medical En	mergency:1-(888)-314-6171 (24 hours)		
Maumee OH 43537	43537 Chemical Leak/Spil Emergency: CHEMTREC 1-(800) 424-9300 (24 hours)				
Shipping Desc	Shipping Description: Gallons & 5 Gallon Pail: ORM-D, Consumer commodity, cleaning compounds, liquid, n.o.s. Drums: Flammable liquids, n.o.s., 3, UN 1993, III, (contains isopropanol)				
NFPA Ratings:			HMIS Ratings:		
Health:	2 - Moderate		Health:	2 - Moderate	
Fire:	Fire: 3 - Serious		Fire:	3 - Serious	
Reactivity:	ivity: 0 - Minimal		Reactivity:	0 - Minimal	
			Pers. Prot. Equip.:	See Section VIII	

SECTION II: HAZARDOUS INGREDIENTS

(Listed when present at 1% or greater, carcinogens at 0.1% or greater) All component chemicals are listed or exempted from listing on the "TSCA Inventory" of chemical substances maintained by the U.S. Environmental Protection Agency.

			Table Z- 1 - A			NTP, IARC
Chemical Name(s)	% W	CAS Registry No.	TWA mg/m ³	STEL mg/m ³	CELING mg/m ³	or OSHA Carcinogen
Isopropyl alcohol	15-20	67-63-0	980	1225	Not Established	No
Propylene glycol monomethyl ether	5-10	107-98-2	369 (ACGIH)	553 (ACGIH)	Not Established	No

SECTION III: PHYSICAL DATA

Boiling Point:	184 °F	Vapor Pressure:	Unknown	
Vapor Density (AIR = 1):	Unknown	Solubility in Water:	Complete	
pH:	9.0-10	Specific Gravity (H ₂ O=1):	0.96 (8.06 pounds per gallon)	
Evaporation Rate (but.ace.=1):	<1	Percent Solid by Weight:	< 1.0%	
Physical State:	Liquid			
Appearance & Odor: Pale green liquid with solvent odor				

SECTION IV: FIRE & EXPLOSIVE HAZARD DATA

Flash Point:	97°F	Method Used:	ASTM-D56	
Flammable Limits:	Not Established	Flame Extension:	N/A	
Extinguishing Media:	Alcohol resistant foam, CO2, Dr	ry Chemical, Water Fog, Wa	ter Spray.	
Special Fire Fighting Procedures:	Use water spray for cooling.			
	Flammable liquid and vapor. Vapors may travel along ground and settle in low areas or be moved by ventilation and be ignited by heat, sparks, pilot lights or other flames and ignition sources. Extinguish all flames, pilot lights and other sources of ignition prior to use and until all vapors are dissipated.			

SECTION V: HEALTH HAZARD DATA

Threshold Limit Value:	Not Established	Primary Routes of Entry: Inhalation, Skin Contact, Eyes, Ingestion		
	Harmful if swallowed: Sympton Inhalation of product vapors of include coughing and difficulty b Do not get in eyes, on skin, or	: Symptoms may include pain, redness, swelling and tearing ms may include nausea, vomiting, pain and diarrhea. r mist may cause respiratory irritation: Symptoms may breathing. on clothing. Avoid breathing product vapor or mist. Do XDM. YHOMDWRQ.: DVK. WRURXJ KQ. DI WUKDQGDQJ.		
Conditions Aggravated by Use:	Use of this product may aggravate preexisting skin; eye and respiratory disorders including asthma and dermatitis.			
Emergency & First Aid Procedu	res:			
Eyes:	Flush eyes with plenty of water attention.	for at least 15 minutes. Remove contact lenses. Get medical		
Skin:		Wash skin thoroughly with soap and water. Get medical ash contaminated clothing before reuse.		
Ingestion:		ne or two glasses of water to dilute product. Get immediate nything by mouth to an unconscious person.		
Inhalation:	Move person to fresh air. If irrit	ation persists; get medical attention.		

SECTION VI: REACTIVITY DATA

Stability:	Stable	Incompatible Materials:	Strong oxidizing substances.
Hazardous Decomposition Products:	Unknown	Hazardous Polymerization:	Will Not Occur

SECTION VII: SPILL OR LEAK PROCEDURES

Steps to be Taken in Case	Eliminate sources of ignition. Small spills can be flushed with large amounts of water to a
Material is Released or Spilled:	sanitary sewer. Contain large spills with sand, earth or other inert absorbent. Do not use
	combustible materials such as sawdust. If warranted by large spill, warn and evacuate
	occupants. In addition, it is recommended that local authorities be contacted to determine if
	there are other local reporting requirements.
Waste Disposal Method:	Consult an expert on disposal of recovered material and ensure conformity with Federal,
	State and Local regulations.

SECTION VIII: SPECIAL PROTECTION INFORMATION

Respiratory Protection:	Not normally required when good general ventilation is provided. However if exposure limits are exceeded (see Section II) or if respiratory irritation occurs, the use of a NIOSH approved respirator suitable for the use-conditions and chemicals listed in Section II should be considered.
Ventilation:	Provide good general ventilation. Local exhaust ventilation may be necessary for some operations.
Protective Gloves(Specify Type):	Rubber or other impervious gloves
Eye Protection(Specify Type):	Splash goggles
Other Protective Equipment:	See 29 CFR 1910.132-138 for further guidance.

SECTION IX: SPECIAL PRECAUTIONS

	Flammable liquid and vapor. Flash point 97 ⁰ F. Keep away from heat, sparks and flame. Do not smoke while using this product. Store in a cool, dry place. Keep container closed. Empty containers retain product residue and explosive vapors. Do not cut, weld or expose such containers to heat, flames, sparks or other sources of ignition.
Other Precautions:	Keep out of reach of children.

© SCC 11/01/2007 aquasport wood floor cleaner	Name: Effective Date:	Ronald T. Cook 11/01/2007	Title: Supercedes:	Manager, Regulatory Affairs 06/30/2005
Pof. 20 CEP 1010 1200 (OSHA)		Undata Saction I		

Ref: 29 CFR 1910.1200 (OSHA) Changes: Update Section I

This document has been prepared using data from sources considered technically reliable. It does not constitute a warranty, express or implied, as to the accuracy of the information contained herein. Actual conditions of use and handling are beyond sellers control. User is responsible to evaluate all available information when using product for any particular use and to comply with all Federal, State and Local laws and regulations.